(R)

INSERT INSTALLATION TECHNOLOGY

Model PH Platen-style Multi-tip Heat Insert Driver



The **SPIROL** Model PH Heat Insert Driver provides an accurate and consistent method to simultaneously install multiple Inserts or Compression Limiters at multiple elevations. Simultaneous installation dramatically increases productivity and simplifies the number of manufacturing steps to complete an assembly. Additionally, the platen head and fixture can be easily

changed to accommodate quick change-over to different assemblies associated with new production runs.

This machine can be used to install 12 Inserts into one assembly, or a fewer number of Inserts into a larger number of assemblies, as long as the total combination does not exceed 12 Inserts. For example, it can simultaneously install 4 Inserts into 3 different assemblies, or 5 Inserts into one assembly and 7 Inserts into another assembly – any combination up to 12 Inserts.

Designed to simultaneously install Heat/Ultrasonic style Inserts at multiple elevations

Design Features/Benefits:

Accurate: - Easily adjustable temperature setting with

Hi-Low temperature lock-out for optimal melt and flow of plastic

- Micrometer style insertion depth adjustment and individually adjustable heat tips for precise positioning of the Inserts or Compression Limiters in the part

Pneumatic operation, with pressure regulator and flow controls to precisely control the

insertion force and speed

- Precise and easy to use timer for installation

quality and consistency

Versatile: - Installs virtually any size Insert and Compression Limiter

- Can be equipped with or without heated tips

- Easily interchangeable platen-style head with

plug-in style heater wiring

- Individual depth-adjustable heat tips to accommodate a wide range of product

configurations

- Heavy-duty twin post mount style frame is easily raised or lowered to accept various

part sizes

Efficient: -Simultaneously installs up to 12 Inserts or Compression Limiters on different levels

- Linear slide fixture with shot pin lock, integral

activation for ease of part loading

Safe: - Guarded pinch points

- Silent operation eliminates harsh noise Quiet: associated with ultrasonic installation

methods

Manual and other automated installation machines are also available from SPIROL.

SPIROL Application Engineering



A molder of plastic electrical conduit components had been experiencing difficulty installing brass Inserts into their products. The Inserts were being installed with an ultrasonic welder. Installation was difficult and the quality was poor due to undersized holes in the components and an unconventional Insert shape. The result was excess molten plastic at the

top of the installed Insert which created an unsightly appearance. In addition, oftentimes the Insert was not in the proper location due to the incorrect hole sizes. Secondary operations were required to remove the excess plastic, and a high percentage of parts were rejected. The production rate was one finished part per minute; sometimes longer depending on the complexity of the part. There are two Inserts per part.

Solution:

SPIROL Engineering reviewed the details of the assembly, and recommended replacing the current custom Inserts with SPIROL's standard INS 29 symmetrical Inserts and the use of SPIROL's Model PH Platen Style Heat Insertion System for installation. The conductive heat method with consistent pneumatic installation pressure resulted in extremely high quality installations with an excellent appearance of the finished parts, and superior performance of the Inserts. The process yielded six completed assemblies in the time that it previously took to complete one. This productivity improvement alone, not including the elimination of scrap, allowed the machine to pay for itself in less than one year.

The machine was provided with quick-change tooling sets to allow the assembly of ten different style parts. Each tooling set was designed to accommodate three to six electrical conduits; depending on their size. The operator can load up to six parts at a time, and install all twelve Inserts simultaneously. When the customer expands their product line, additional tooling sets can easily be added to accommodate new parts as they are designed and marketed.

SPIROL offers complimentary Application Engineering support. We will assist on new designs as well as help resolve issues, and recommend cost savings on existing designs. Let us help by visiting Application Engineering Services on SPIROL.com.

Technical Centers

Americas

SPIROL International Corporation

30 Rock Avenue

Danielson, Connecticut 06239 U.S.A.

Tel. +1 860 774 8571 Fax. +1 860 774 2048

SPIROL Shim Division

321 Remington Road Stow, Ohio 44224 U.S.A. Tel. +1 330 920 3655 Fax. +1 330 920 3659

SPIROL Canada

3103 St. Etienne Boulevard Windsor, Ontario N8W 5B1 Canada Tel. +1 519 974 3334

Fax. +1 519 974 6550

SPIROL Mexico

Avenida Avante #250 Parque Industrial Avante Apodaca Apodaca, N.L. 66607 Mexico Tel. +52 81 8385 4390 Fax. +52 81 8385 4391

SPIROL Brazil

Rua Mafalda Barnabé Soliane, 134 Comercial Vitória Martini, Distrito Industrial CEP 13347-610, Indaiatuba, SP, Brazil Tel. +55 19 3936 2701 Fax. +55 19 3936 7121

Europe

SPIROL France

Cité de l'Automobile ZAC Croix Blandin 18 Rue Léna Bernstein 51100 Reims, France Tel +33 3 26 36 31 42 Fax. +33 3 26 09 19 76

SPIROL United Kingdom

17 Princewood Road Corby, Northants NN17 4ET United Kingdom Tel. +44 1536 444800 Fax. +44 1536 203415

SPIROL Germany

Ottostr. 4 80333 Munich, Germany Tel. +49 89 4 111 905 71 Fax. +49 89 4 111 905 72

SPIROL Spain

08940 Cornellà de Llobregat Barcelona, Spain Tel. +34 93 669 31 78 Fax. +34 93 193 25 43

SPIROL Czech Republic

Pražská1847 274 01 Slaný Czech Republic Tel. +420 313 562 283

SPIROL Poland

Aleia 3 Maia 12 00-391 Warszawa, Poland Tel. +48 510 039 345

Asia Pacific

SPIROL Asia Headquarters

1st Floor, Building 22, Plot D9, District D No. 122 HeDan Road Wai Gao Qiao Free Trade Zone Shanghai, China 200131 Tel. +86 21 5046 1451 Fax. +86 21 5046 1540

SPIROL Korea

160-5 Seokchon-Dong Songpa-gu, Seoul, 138-844, Korea Tel. +86 (0) 21 5046-1451 Fax. +86 (0) 21 5046-1540

e-mail: info@spirol.com

SPIROL.com